

Package: epiflows (via r-universe)

October 4, 2026

Title Predicting Disease Spread from Flow Data

Version 0.2.1

Description Provides functions and classes designed to handle and visualise epidemiological flows between locations. Also contains a statistical method for predicting disease spread from flow data initially described in Dorigatti et al. (2017) <doi:10.2807/1560-7917.ES.2017.22.28.30572>. This package is part of the RECON (<<https://www.repidemicsconsortium.org/>>) toolkit for outbreak analysis.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.4.0)

Imports epicontacts, leaflet, ggmap, geosphere, ggplot2, tibble, sp, stats, htmltools, visNetwork

Suggests testthat, roxygen2, knitr, outbreaks, vdiff, curl, rmarkdown

RoxygenNote 7.2.3

URL <https://www.repidemicsconsortium.org/epiflows/>,
<https://github.com/reconhub/epiflows>

BugReports <https://github.com/reconhub/epiflows/issues>

VignetteBuilder knitr

Config/pak/sysreqs
libabsl-dev cmake libgdal-dev gdal-bin libgeos-dev libglpk-dev make libicu-dev libjpeg-dev libpng-dev libuv1-dev libxml2-dev libssl-dev libproj-dev libsqlite3-dev libudunits2-dev

Repository <https://epiverse-connect.r-universe.dev>

Date/Publication 2023-09-20 10:14:38 UTC

RemoteUrl <https://github.com/reconhub/epiflows>

RemoteRef HEAD

RemoteSha 2fdb4d22d82b4471872e2a805d3b3126eceed672

Contents

[.epiflows	2
add_coordinates	3
as.SpatialLinesDataFrame	5
epiflows	5
estimate_risk_spread	6
get_flows	9
get_id	10
get_locations	11
get_n	12
get_pop_size	13
get_vars	13
global_vars	15
grid_epiflows	17
make_epiflows	17
map_epiflows	20
plot.epiflows	21
print.epiflows	22
vis_epiflows	23
YF_Brazil	23
Index	26

[.epiflows	<i>Subset 'epiflows' objects</i>
------------	----------------------------------

Description

An epiflows object inherits the epicontacts class, so the subsetting mechanism is also inherited. The benefits is that it's extremely flexible. However, this also means that it's possible for the contacts to contain IDs that are not present in the locations metadata and vice versa. The best way to consistently subset an epiflows object is present in the examples.

Usage

```
## S3 method for class 'epiflows'
x[i, j, k = TRUE, l = TRUE, ...]
```

Arguments

x	An epiflows object.
i	An integer, logical, or character vector of one or more location.
j	An integer, logical, or character vector to subset the flows data frame.
k	A character vector of one or more columns to be retained in the location data.
l	A character vector of one or more columns to be retained in the flows data frame.
	Note: if using numbers, the first column stands for the first column after "n".
...	Additional parameters passed to [.epicontacts] .

Details

Returns a subset of an epiflows object.

Value

An epiflows object.

Author(s)

Zhian N. Kamvar

Examples

```
data(Brazil_epiflows)
# You can subset, but the flows information will still be present
Brazil_epiflows[j = "Espirito Santo"]
# To help with this, use `thin` from epiflows
epicontacts::thin(Brazil_epiflows[j = "Espirito Santo"])
epicontacts::thin(Brazil_epiflows[j = c("Espirito Santo", "Rio de Jenerio")])
```

add_coordinates

Add/Retrieve location coordinates

Description

Adds/Retrieves longitude/latitude values to location data within an epiflows object. Coordinates are added to object's locations slot as lon and lat columns.

Usage

```
add_coordinates(
  x,
  coordinates = c("lon", "lat"),
  loc_column = "id",
  overwrite = FALSE
)

get_coordinates(x, ...)

## S3 method for class 'epiflows'
get_coordinates(x, location = NULL, ...)
```

Arguments

<code>x</code>	An epiflows object.
<code>coordinates</code>	Either names of the appended columns with longitudes and latitudes, respectively (default: "lon" and "lat") or a data frame with longitude and latitude columns.
<code>loc_column</code>	Name of the column where location names are stored (default: "country").
<code>overwrite</code>	If TRUE, retrieves all geocodes, even those already retrieved. If FALSE (default), overwrites only NAs.
<code>...</code>	unused
<code>location</code>	a character specifying a single location to return as a vector of coordinates. You cannot specify multiple locations with this parameter. Defaults to 'NULL', indicating all locations.

Value

An updated epiflows object.

Author(s)

Pawel Piatkowski, Salla Toikkanen, Zhian Kamvar

See Also

`map_epiflows()`; `plot_epiflows()`; `get_locations()`; `get_vars()`; `global_vars()`

Examples

```
# Setting up the data
data("Brazil_epiflows")
data("YF_coordinates")
get_coordinates(Brazil_epiflows) # no coordinates yet
ef <- add_coordinates(Brazil_epiflows, YF_coordinates[-1])
get_coordinates(ef)
get_coordinates(ef, location = "Espirito Santo") # coordinates for Espirito Santo
if (interactive()) {
  # You can use google maps' geocode functionality if you have a decent
  # internet connection
  # NOTE: you may need to authenticate with Google Maps API beforehand
  # using ggmap::register_google()
  ef2 <- add_coordinates(Brazil_epiflows, loc_column = "id")
  ef2
}
```

as.SpatialLinesDataFrame	<i>Convert to SpatialLinesDataFrame class</i>
--------------------------	---

Description

Convert to SpatialLinesDataFrame class

Usage

```
as.SpatialLinesDataFrame(x)

## S3 method for class 'epiflows'
as.SpatialLinesDataFrame(x)
```

Arguments

x an epiflows object

Value

an object of class [sp::SpatialLinesDataFrame]

Examples

```
data("Brazil_epiflows")
data("YF_coordinates")
ef <- add_coordinates(Brazil_epiflows, YF_coordinates[-1])
ef2 <- epicontacts::thin(ef[j = c("Espirito Santo", "Italy"), contacts = "both"])
as.SpatialLinesDataFrame(ef2)
```

epiflows	<i>epiflows</i>
----------	-----------------

Description

epiflows is a package for predicting and visualising spread of infectious diseases based on flows between geographical locations, e.g., countries. epiflows provides functions for calculating spread estimates, handling flow data, and visualization.

Details

The main functions of the package are `make_epiflows()` for constructing an epiflows object and `estimate_risk_spread()` to estimate potential spread. Visualization is available for maps, networks, and grids.

For details, see the vignettes:

```
vignette("introduction", package = "epiflows")
vignette("epiflows-class", package = "epiflows")
```

estimate_risk_spread	<i>Travel-related disease cases spreaded to other locations from an infectious location</i>
----------------------	---

Description

Calculates the mean and 95% confidence interval of the estimated number of disease cases that could potentially seed a disease outbreak in the locations they are travelling to, comprising exportations (infected residents of the infectious location travelling abroad during the incubation or infectious period), and importations (international tourists infected by the disease during their stay in the infectious location and returning to their home location). The mean and 95% confidence intervals are obtained by numerically sampling `n_sim` times from the incubation and infectious period distributions. If parameter `return_all_simulations` is set to `TRUE`, the function returns all simulations for each location.

Usage

```
estimate_risk_spread(...)

## Default S3 method:
estimate_risk_spread(
  location_code = character(0),
  location_population = numeric(0),
  num_cases_time_window = numeric(0),
  first_date_cases = character(0),
  last_date_cases = character(0),
  num_travellers_to_other_locations = numeric(0),
  num_travellers_from_other_locations = numeric(0),
  avg_length_stay_days = numeric(0),
  r_incubation = function(n) {
  },
  r_infectious = function(n) {
  },
  n_sim = 1000,
  return_all_simulations = FALSE,
  ...
)
```

```
## S3 method for class 'epiflows'
estimate_risk_spread(
  x,
  location_code = character(0),
  r_incubation = function(n) {
  },
  r_infectious = function(n) {
  },
  n_sim = 1000,
  return_all_simulations = FALSE,
  ...
)
```

Arguments

...	Arguments passed onto the default method.
location_code	a character string denoting the infectious location code
location_population	population of the infectious location
num_cases_time_window	cumulative number of cases in infectious location in time window
first_date_cases	string with the date of the first disease case in infectious location ("YYYY-MM-DD")
last_date_cases	string with the date of the last disease case in infectious location ("YYYY-MM-DD")
num_travellers_to_other_locations	number of travellers from the infectious location visiting other locations (T_D)
num_travellers_from_other_locations	number of travellers from other locations visiting the infectious location (T_O)
avg_length_stay_days	average length of stay in days of travellers from other locations visiting the infectious location. This can be a common number for all locations or a vector with different numbers for each location
r_incubation	a function with a single argument n generating 'n' random incubation periods
r_infectious	a function with a single argument n generating 'n' random durations of infectious period
n_sim	number of simulations from the incubation and infectious distributions
return_all_simulations	logical value indicating whether the returned object is a data frame with all simulations (return_all_simulations = TRUE) or a data frame with the mean and lower and upper limits of a 95% confidence interval of the number of cases spread to each location (return_all_simulations = FALSE)
x	an epiflows object

Value

if `return_all_simulations` is `TRUE`, data frame with all simulations. If `return_all_simulations` is `FALSE`, data frame with the mean and lower and upper limits of a 95% confidence interval of the number of cases spread to each location

Author(s)

Paula Moraga, Zhian Kamvar (epiflows class implementation)

References

Dorigatti I, Hamlet A, Aguas R, Cattarino L, Cori A, Donnelly CA, Garske T, Imai N, Ferguson NM. International risk of yellow fever spread from the ongoing outbreak in Brazil, December 2016 to May 2017. *Euro Surveill.* 2017;22(28):pii=30572. DOI: [doi:10.2807/15607917.ES.2017.22.28.30572](https://doi.org/10.2807/15607917.ES.2017.22.28.30572)

See Also

Construction of epiflows object: [make_epiflows\(\)](#)
 Default variables used in the epiflows implementation: [global_vars\(\)](#)
 Access metadata from the epiflows object: [get_vars\(\)](#)

Examples

```
## Using an epiflows object -----

data("YF_flows")
data("YF_locations")
ef <- make_epiflows(flows      = YF_flows,
                   locations   = YF_locations,
                   pop_size    = "location_population",
                   duration_stay = "length_of_stay",
                   num_cases    = "num_cases_time_window",
                   first_date   = "first_date_cases",
                   last_date    = "last_date_cases"
)
## functions generating incubation and infectious periods
incubation <- function(n) {
  rlnorm(n, 1.46, 0.35)
}

infectious <- function(n) {
  rnorm(n, 4.5, 1.5/1.96)
}

res <- estimate_risk_spread(ef,
                           location_code = "Espirito Santo",
                           r_incubation  = incubation,
                           r_infectious  = infectious,
                           n_sim         = 1e5,
                           return_all_simulations = TRUE)

boxplot(res, las = 3)
```

```
## Using other data -----
data(YF_Brazil)
indstate <- 1 # "Espírito Santo" (indstate = 1),
             # "Minas Gerais" (indstate = 2),
             # "Southeast Brazil" (indstate = 5)

res <- estimate_risk_spread(
  location_code = YF_Brazil$states$location_code[indstate],
  location_population = YF_Brazil$states$location_population[indstate],
  num_cases_time_window = YF_Brazil$states$num_cases_time_window[indstate],
  first_date_cases = YF_Brazil$states$first_date_cases[indstate],
  last_date_cases = YF_Brazil$states$last_date_cases[indstate],
  num_travellers_to_other_locations = YF_Brazil$T_D[indstate,],
  num_travellers_from_other_locations = YF_Brazil$T_O[indstate,],
  avg_length_stay_days = YF_Brazil$length_of_stay,
  r_incubation = incubation,
  r_infectious = infectious,
  n_sim = 100000,
  return_all_simulations = FALSE
)
head(res)
```

get_flows

Access flow data

Description

This accessor extract flow data from an epiflows object. `get_flows` is a generic with a method defined for epiflows objects.

Usage

```
get_flows(x, ...)
```

```
## S3 method for class 'epiflows'
get_flows(x, from = NULL, to = NULL, all = FALSE, ...)
```

Arguments

<code>x</code>	An ‘epiflows’ object.
<code>...</code>	unused
<code>from</code>	a character string defining which regions should be included in the flows
<code>to</code>	a character string defining which regions should be included in the flows
<code>all</code>	when ‘TRUE’, all the columns of the flows data frame will be returned. Defaults to ‘FALSE’, which returns "from", "to", and "n".

Value

A data.frame with 3 columns:

- from: origin of the flow
- to: destination of the flow
- n: magnitude of the flow—can be a number of passengers per unit of time, a rate, a probability of migration

Author(s)

Zhian N. Kamvar

See Also

[get_n\(\)](#); For location metadata: [get_locations\(\)](#), [get_vars\(\)](#), [get_pop_size\(\)](#), [get_coordinates\(\)](#)

Examples

```
data("Brazil_epiflows")
head(get_flows(Brazil_epiflows))
get_flows(Brazil_epiflows, from = "Minas Gerais")
get_flows(Brazil_epiflows, to = "Minas Gerais")
get_flows(Brazil_epiflows, from = "Italy", to = "Minas Gerais")
```

get_id

Access population identifiers in epiflows objects

Description

this will return the unique population ID for your epiflows object.

Usage

```
get_id(x, ...)
```

Arguments

x an epiflows object
 ... arguments passed on to [epicontacts::get_id\(\)](#)

Value

a character vector of population IDs

Author(s)

Zhian N. Kamvar

See Also

[epicontacts::get_id\(\)](#); [get_vars\(\)](#); [get_pop_size\(\)](#); [global_vars\(\)](#)

Examples

```
data("Brazil_epiflows")
get_id(Brazil_epiflows)
```

get_locations	<i>Access flow data</i>
---------------	-------------------------

Description

This accessor extract location data from an epiflows object. `get_locations` is a generic with a method defined for epiflows objects.

Usage

```
get_locations(x, ...)

## S3 method for class 'epiflows'
get_locations(x, ...)
```

Arguments

<code>x</code>	An epiflows object.
<code>...</code>	unused

Value

A `data.frame` with at least 1 column called `id`, specifying the id of the location used in the flows data frame.

Author(s)

Thibaut Jombart, Zhian Kamvar

See Also

[get_flows\(\)](#); [get_id\(\)](#); [get_pop_size\(\)](#); [get_vars\(\)](#); [get_coordinates\(\)](#); [global_vars\(\)](#)

Examples

```
data("Brazil_epiflows")
get_locations(Brazil_epiflows)
```

get_n	<i>get the number of cases per flow</i>
-------	---

Description

This convenience function will return a named vector containing the number of cases flowing to or from a given region.

Usage

```
get_n(x, from = NULL, to = NULL, ...)
```

```
## S3 method for class 'epiflows'
get_n(x, from = NULL, to = NULL, ...)
```

Arguments

x	an epiflows object
from	a character vector of length one specifying the location from which the flows originate
to	a character vector of length one specifying the location to which the flows terminate
...	unused

Details

There are three possible outputs of this function:

- **no options specified:** an un-named vector, equivalent to `get_flows(x)$n`
- **from = X:** a named vector of cases flowing *from* X
- **to = X:** a named vector of cases flowing *to* X

Value

a character vector

See Also

[get_flows\(\)](#); For location metadata: [get_vars\(\)](#), [get_pop_size\(\)](#), [get_coordinates\(\)](#)

Examples

```
data(Brazil_epiflows)
get_n(Brazil_epiflows, from = "Espirito Santo")
get_n(Brazil_epiflows, to = "Espirito Santo")
```

get_pop_size	<i>Get population size for each entry in locations</i>
--------------	--

Description

Get population size for each entry in locations

Usage

```
get_pop_size(x)

## S3 method for class 'epiflows'
get_pop_size(x)
```

Arguments

x an epiflows object

Value

a named vector of population sizes

See Also

[get_vars\(\)](#), [global_vars\(\)](#)

Examples

```
data("Brazil_epiflows")
get_pop_size(Brazil_epiflows)
```

get_vars	<i>Access location metadata</i>
----------	---------------------------------

Description

This accessor extracts variables from the locations data frame in an epiflow object. `get_vars` is a generic with a method defined for epiflows objects.

Usage

```

get_vars(x, ...)

## S3 method for class 'epiflows'
get_vars(x, what = NULL, id = TRUE, vector = FALSE, ...)

set_vars(x, ...)

set_vars(x, name) <- value

## S3 method for class 'epiflows'
set_vars(x, ...)

## S3 replacement method for class 'epiflows'
set_vars(x, name) <- value

```

Arguments

x	An epiflows object.
...	For set_vars(), any number of variables defined in global_vars() that can be used for mapping or modelling. This is unused in get_vars()
what	a valid character string specifying the variable desired. If 'NULL' (default), the names of the available vars will be returned.
id	a logical. If 'TRUE' (default), the 'id' column of the locations will be the first column of the data frame. if 'FALSE', the variable will be returned with identifiers as row names.
vector	if 'TRUE' the result will be coerced into a vector (or a matrix in the case of coordinates)
name	the name of the variable in global_vars() to assign
value	the name of the column in the locations data

Value

A data frame with the variables requested

Author(s)

Thibaut Jombart, Zhian Kamvar

See Also

[global_vars\(\)](#); [make_epiflows\(\)](#); [get_pop_size\(\)](#); [get_id\(\)](#)

Examples

```
data("Brazil_epiflows")
get_vars(Brazil_epiflows) # defined global variables pointint to column names
get_vars(Brazil_epiflows, "duration_stay")
get_vars(Brazil_epiflows, "duration_stay", vector = TRUE)
```

global_vars

*Epiflow Global Variables***Description**

The metadata in **locations** such as population size, duration of stay in a given location, date of first and last cases, etc. can be useful in estimating the risk of spread, but not everyone will code their data with identical column names. To facilitate their use in the function `estimate_risk_spread()`, the epiflows object stores a dictionary of variables in a place called `$vars`. We can tell epiflows what variables are important when we create the object.

Usage

```
global_vars(..., set = FALSE, reset = FALSE)
```

Arguments

<code>...</code>	quoted variables to add to the default variables
<code>set</code>	when TRUE, the variables provided in <code>...</code> will be added to the global variables. Defaults to FALSE
<code>reset</code>	when TRUE, the global variables are reset to the default variables listed above. Defaults to FALSE

Details

The default variables are:

- `coordinates`: two columns specifying the lon and lat coordinates
- `pop_size`: population size of each location
- `duration_stay`: the average duration of stay for each location
- `first_date`: the date of first recorded case
- `last_date`: the date of the last recorded case
- `num_cases`: the number of cases between the first and last date

See Also

[make_epiflows\(\)](#), [get_locations\(\)](#), [get_vars\(\)](#), [set_vars\(\)](#), [get_coordinates\(\)](#)

Examples

```
# see the default variables
global_vars()

# Equivalent
getOption("epiflows.vars")

# create an object, specifying these variables
data("YF_locations")
data("YF_flows")
ef <- make_epiflows(flows      = YF_flows,
                   locations   = YF_locations,
                   pop_size    = "location_population",
                   duration_stay = "length_of_stay",
                   num_cases   = "num_cases_time_window",
                   first_date   = "first_date_cases",
                   last_date    = "last_date_cases"
                  )

ef

# You will receive an error if a variable is specified incorrectly
YF_locations$random_variable <- runif(nrow(YF_locations))
try({
  ef <- make_epiflows(flows      = YF_flows,
                     locations   = YF_locations,
                     Pop_size    = "location_population",
                     duration_stay = "length_of_stay",
                     num_cases   = "num_cases_time_window",
                     first_date   = "first_date_cases",
                     last_date    = "last_date_cases",
                     random       = "random_variable"
                    )
})

# If you create a new method and need other variables, or just want a shorter
# representation, they can be added to your options:

global_vars("random", set = TRUE)

YF_locations$random_variable <- runif(nrow(YF_locations))
ef <- make_epiflows(flows      = YF_flows,
                   locations   = YF_locations,
                   pop_size    = "location_population",
                   duration_stay = "length_of_stay",
                   num_cases   = "num_cases_time_window",
                   first_date   = "first_date_cases",
                   last_date    = "last_date_cases",
                   random       = "random_variable"
                  )
```

```
# You can also reset the variables
global_vars(reset = TRUE)
```

grid_epiflows	<i>Visualise epidemic flows using a grid</i>
---------------	--

Description

This grid plot shows flows between locations by positioning origins and destination in y and x axes, respectively. This function is called when plotting epiflows with `type = "grid"`.

Usage

```
grid_epiflows(x, color_by = c("from", "to", "none"), ...)
```

Arguments

<code>x</code>	An epiflows object.
<code>color_by</code>	A character string indicating if flows should be colored by origin (from) or destination (to).
<code>...</code>	arguments passed on to <code>ggplot2::geom_point()</code>

Author(s)

Thibaut Jombart

make_epiflows	<i>Create an epiflows object</i>
---------------	----------------------------------

Description

An epiflows object contains a pair of data frames that provide information about locations and flows between locations.

Usage

```
make_epiflows(...)

## S3 method for class 'data.frame'
make_epiflows(
  flows,
  locations = NULL,
  from = 1L,
  to = 2L,
  n = 3L,
```

```

    id = 1L,
    ...
)

## S3 method for class 'integer'
make_epiflows(inflow, outflow, focus, locations, id = 1L, ...)

## S3 method for class 'numeric'
make_epiflows(inflow, outflow, focus, locations, id = 1L, ...)

```

Arguments

...	Any number of variables that can be used for mapping or modelling. See global_vars() and get_vars() for details.
flows	a data frame where each row represents a flow from one location to the next. This must have at least three columns: • Where the flow started (as specified in <code>from</code>, below) • Where the flow ended (as specified in <code>to</code>, below) • How many cases were involved (as specified in <code>n</code>, below)
locations	a data frame where each row represents a location. This can have any number of columns specifying useful metadata about the location, but it must contain at least one column specifying the location ID used in the <code>flows</code> data frame (as specified by the <code>id</code> argument, below).
from	the column in the <code>flows</code> data frame indicating where the flow started. This can be an integer or character. Default is the first column.
to	the column in the <code>flows</code> data frame indicating where the flow terminated. This can be an integer or character. Default is the second column.
n	the column in the <code>flows</code> data frame indicating how many cases were contained in the flow. This can be an integer or character. Default is the third column.
id	The column to use for the identifier in the <code>locations</code> data frame. This defaults to the first column.
inflow	a named integer or numeric vector specifying the number of cases flowing into a location specified by <code>focus</code> .
outflow	a named integer or numeric vector specifying the number of cases flowing from a location specified by <code>focus</code> .
focus	a character vector specifying the focal location for integer input. This is necessary for integer input to make clear what "outflow" and "inflow" are relative to.

Details

The `epiflows` object can be constructed using simply a list of locations with optional metadata (similar to a `linelist`) and a list of flows that describes the number of cases flowing from one location to another. Optional metadata such as coordinates and duration of stay can be included in the `linelist` for use in [estimate_risk_spread\(\)](#) or [map_epiflows\(\)](#).


```

        last_date      = "last_date_cases"
      )
    ef
    # Access variable information
    get_pop_size(ef)
    get_vars(ef, "duration_stay")
    get_vars(ef, "num_cases")
    data(YF_Brazil)
    (inflows  <- YF_Brazil$T_0["Espirito Santo", , drop = TRUE])
    (outflows <- YF_Brazil$T_D["Espirito Santo", , drop = TRUE])
    (locations <- subset(YF_Brazil$states, location_code == "Espirito Santo", drop = FALSE))
    los <- data.frame(location_code = names(YF_Brazil$length_of_stay),
                      length_of_stay = YF_Brazil$length_of_stay,
                      stringsAsFactors = FALSE
    )
    locations <- merge(x = locations,
                      y = los,
                      by = "location_code",
                      all = TRUE)
    ef <- make_epiflows(inflow = inflows,
                      outflow = outflows,
                      focus = "Espirito Santo",
                      locations = locations,
                      pop_size = "location_population",
                      duration_stay = "length_of_stay",
                      num_cases = "num_cases_time_window",
                      first_date = "first_date_cases",
                      last_date = "last_date_cases"
    )
  ef

```

map_epiflows

Map flows of people between locations

Description

The function `map_epiflows` uses `leaflet` to generate an interactive map displaying flows of people travelling between locations stored in a `epiflows` object. Note that the object needs to possess geographic coordinates.

Usage

```

map_epiflows(
  x,
  title = "",
  center = NULL,
  sort = TRUE,
  pal = "YlOrBr",
  adjust_width = TRUE,
  ...
)

```

Arguments

x	An epiflows object.
title	Plot title.
center	An optional set of coordinates or character string specifying ID to use as the center of the map
sort	a logical. When TRUE (default), the flows will be sorted in order of number of cases on the map so that the largest flows appear on top.
pal	a color palette to pass on to <code>leaflet::colorQuantile()</code> . This can be the name of a viridis or RColorBrewer palette, a vector of hex colors, or a color-generating function.
adjust_width	a logical specifying if the width of the flows should be adjusted to reflect the number of flows between locations. Defaults to TRUE.
...	Additional parameters (not used).

Value

A leaflet object

Author(s)

Paula Moraga, Pawel Piatkowski, Salla Toikkanen, Zhian Kamvar

Examples

```
data("Brazil_epiflows")
data("YF_coordinates")
ef <- add_coordinates(Brazil_epiflows, YF_coordinates[-1])
plot(ef)
map_epiflows(ef, center = "Espirito Santo", title = "Flows to and from Brazil")
```

plot.epiflows	<i>Various plots for epiflows objects</i>
---------------	---

Description

The plot method for epiflows objects offers types of graphics (argument type):

Usage

```
## S3 method for class 'epiflows'
plot(x, type = c("map", "network", "grid"), ...)
```

Arguments

x	an epiflows object.
type	The type of plot to produce (defaults to map).
...	arguments passed on to a given type

Details

- map: flows are displayed on an interactive map; see [map_epiflows](#) for more details
- network: flows are displayed as a network using the htmlwidget visNetwork and the plotting method for epicontacts objects; see [vis_epiflows](#) for more details
- grid: flows are displayed as a grid between origins and destinations; see [grid_epiflows](#) for more details

Author(s)

Salla Toikkanen, Thibaut Jombart, Zhian Kamvar

Examples

```
data("Brazil_epiflows")

# no coordinates, defaults to network
plot(Brazil_epiflows)

# grid bubbleplot
plot(Brazil_epiflows, "grid")

# adding coordinates defaults to map
data("YF_coordinates")
ef <- add_coordinates(Brazil_epiflows, YF_coordinates[-1])
plot(ef)
```

print.epiflows	<i>Print method from epiflows objects</i>
----------------	---

Description

Displays a short summary of an epiflows object.

Usage

```
## S3 method for class 'epiflows'
print(x, ...)
```

Arguments

x	An epiflows object.
...	Additional parameters (not used).

Author(s)

Zhian N. Kamvar, Thibaut Jombart

Examples

```
data("Brazil_epiflows")
print(Brazil_epiflows)
```

vis_epiflows

*Visualise epidemic flows using visNetwork***Description**

This function shows flows between locations using a dynamic network visualisation implemented in the package **visNetwork**, calling the function `epicontacts::vis_epicontacts()` of the **epi-contacts** package. The thickness of arrows/edges is proportional to the corresponding flows.

Usage

```
vis_epiflows(x, arrows = TRUE, max_width = 10, ...)
```

Arguments

x	An epiflows object.
arrows	A logical indicating if arrows should be used to show directionality of the flows.
max_width	A single number indicating the maximum width of an edge (corresponding to the largest flow).
...	Further arguments passed to <code>epicontacts::vis_epicontacts()</code>

Author(s)

Thibaut Jombart

YF_Brazil

*Yellow Fever Data from Brazil; 2016-12 to 2017-05***Description**

This data set contains flows to and from five states in Brazil formatted in a list with the following items:

Usage

```
data("Brazil_epiflows")
data("YF_coordinates")
data("YF_locations")
data("YF_flows")
data("YF_Brazil")
```

Format

An object of class `list` of length 4.

Details

- `$states`: a data frame containing metadata for five Brazilian States: Espirito Santo, Minas Gerais, Rio de Janeiro, Sao Paulo, and Southeast Brazil
 - `$location_code`: names of the states
 - `$location_population`: population size for each state
 - `$num_cases_time_window`: number of cases recorded between 2016-12 and 2017-05
 - `$first_date_cases`: date of first disease case in the given location in ISO 8601 format
 - `$last_date_cases`: date of last disease case in the given location in ISO 8601 format
- `$T_D` A matrix containing the number of travellers from the infectious location visiting other locations
- `$T_O` A matrix containing the number of travellers visiting the infectious location
- `$length_of_stay` A named vector containing the average length of stay in days of travellers from other locations visiting the infectious locations.

References

Dorigatti I, Hamlet A, Aguas R, Cattarino L, Cori A, Donnelly CA, Garske T, Imai N, Ferguson NM. International risk of yellow fever spread from the ongoing outbreak in Brazil, December 2016 to May 2017. *Euro Surveill.* 2017;22(28):pii=30572. DOI: [doi:10.2807/15607917.ES.2017.22.28.30572](https://doi.org/10.2807/15607917.ES.2017.22.28.30572)

See Also

`make_epiflows()` for transformation to an `epiflows` object `estimate_risk_spread()`

Examples

```
# This is an example of an epiflows object
data("Brazil_epiflows")
Brazil_epiflows

# The above data was constructed from a data frame containing flows and
# one containing location metadata
data("YF_flows")
data("YF_locations")
ef <- make_epiflows(flows      = YF_flows,
                    locations  = YF_locations,
                    pop_size   = "location_population",
                    duration_stay = "length_of_stay",
                    num_cases   = "num_cases_time_window",
                    first_date   = "first_date_cases",
                    last_date    = "last_date_cases"
                    )

# Both of the above data frames were constructed like so:
```

```
data("YF_Brazil")

# Create the flows data frame
from <- as.data.frame.table(YF_Brazil$T_D, stringsAsFactors = FALSE)
to <- as.data.frame.table(t(YF_Brazil$T_O), stringsAsFactors = FALSE)
flows <- rbind(from, to)
colnames(flows) <- c("from", "to", "n")

## Create the locations data frame
los <- data.frame(location_code = names(YF_Brazil$length_of_stay),
                  length_of_stay = YF_Brazil$length_of_stay,
                  stringsAsFactors = FALSE
                )
locations <- merge(x = YF_Brazil$states,
                  y = los,
                  by = "location_code",
                  all = TRUE)

## Use both to create the epiflows object.
ef <- make_epiflows(flows,
                    locations,
                    pop_size = "location_population",
                    duration_stay = "length_of_stay",
                    num_cases = "num_cases_time_window",
                    first_date = "first_date_cases",
                    last_date = "last_date_cases"
                  )
```

Index

- * **datasets**
 - YF_Brazil, [23](#)
 - [.epicontacts, [2](#)
 - [.epiflows, [2](#)
- add_coordinates, [3](#)
- add_coordinates(), [19](#)
- as.SpatialLinesDataFrame, [5](#)
- Brazil_epiflows (YF_Brazil), [23](#)
- epicontacts::get_id(), [10](#), [11](#)
- epicontacts::make_epicontacts(), [19](#)
- epicontacts::thin(), [19](#)
- epicontacts::vis_epicontacts(), [23](#)
- epiflows, [5](#)
- epiflows.vars (global_vars), [15](#)
- estimate_risk_spread, [6](#)
- estimate_risk_spread(), [6](#), [18](#), [19](#), [24](#)
- get_coordinates (add_coordinates), [3](#)
- get_coordinates(), [10–12](#), [15](#)
- get_flows, [9](#)
- get_flows(), [11](#), [12](#), [19](#)
- get_id, [10](#)
- get_id(), [11](#), [14](#)
- get_locations, [11](#)
- get_locations(), [4](#), [10](#), [15](#), [19](#)
- get_n, [12](#)
- get_n(), [10](#)
- get_pop_size, [13](#)
- get_pop_size(), [10–12](#), [14](#)
- get_vars, [13](#)
- get_vars(), [4](#), [8](#), [10–13](#), [15](#), [18](#), [19](#)
- ggplot2::geom_point(), [17](#)
- global_vars, [15](#)
- global_vars(), [4](#), [8](#), [11](#), [13](#), [14](#), [18](#), [19](#)
- grid_epiflows, [17](#), [22](#)
- leaflet::colorQuantile(), [21](#)
- make_epiflows, [17](#)
- make_epiflows(), [6](#), [8](#), [14](#), [15](#), [24](#)
- map_epiflows, [20](#), [22](#)
- map_epiflows(), [4](#), [18](#)
- plot.epiflows, [21](#)
- plot.epiflows(), [4](#), [19](#)
- print.epiflows, [22](#)
- set_vars (get_vars), [13](#)
- set_vars(), [15](#)
- set_vars<- (get_vars), [13](#)
- vis_epiflows, [22](#), [23](#)
- YF_Brazil, [23](#)
- YF_coordinates (YF_Brazil), [23](#)
- YF_flows (YF_Brazil), [23](#)
- YF_locations (YF_Brazil), [23](#)